

Paper Straw Machine Quotation & Technical parameter HC-BP007

Ite	Product Name	Model	QTY		
1	Auto box packing machine	/	1		
REMARK: Voltage 380v, 50hz, 3ph					

Instruction:	
一. Place of delivery: :	Supplier factory
二. Delivery time:	Within 60 days after receiving down payment
三. Offer valid:	30 days.
四. Payment:	
五. Package:	Stretch Film package
六. Warranty:	According to the nation related regulation, one year from the date of delivery.
七. After-sales service:	
Equipment warranty for one year (Cylinder warranty for three months, belt, shaft, blade are not warranty)	
<ol style="list-style-type: none"> 1. repair for free within 1 year. 2. Give internet technology support and train workers 3. Damage to the machine caused by natural or human-intended disasters, and need to change spare part, we only charge material fare and manual fee. 4. Lift-time warranty 	

Auto box packing machine

Main performance technical parameters:

Packing speed	30-60box/min
Box packing size	L (95-280) mm×W (120-190) mm×H (30-90) mm
Box paper requirement	350-400g/m ³
Specification requirement paper	60-70 g/m ³
Motor power	3.25KW
Voltage	380V 3ph 50Hz
Machine noise	≤80dB
Air supply	0.5-0.7Mpa
Air consumption	120-160L/min
Machine size	L4150×W 1450×H1900mm
Weight	1500Kg

Scope of application:

It is suitable for large-scale products such as oral liquid, egg yolk pie, biscuits, coffee bars, strips, paper towels, paper straw and other large-scale products.

Main performance structure characteristics:

It adopts the packaging forms of automatic feeding, unpacking, folding, inserting, batch numbering, sealing, rejecting, etc. The structure is compact and reasonable, and the operation and adjustment are simple;

Adopt servo/stepping motor and touch screen, PLC programmable control system, man-machine interface display operation is clearer and easier, high degree of automation, more humane;

The photoelectric eye automatic detection and tracking system is adopted, and the empty package can not be dropped into the box, which saves the packaging material to the greatest extent;

Large packaging range, convenient adjustment, and quick conversion between various specifications and sizes;

No need to change molds for changing specifications, only need to adjust to achieve;

It adopts automatic shutdown of items into the box and overload protection device of main drive motor, which is more safe and reliable;

According to customer requirements, the use of flip-up safety shield, easy to operate, beautiful appearance.

Can be linked with aluminum plastic packaging machine, pillow packaging machine, three-dimensional packaging machine, bottling line, filling machine, labeling machine, inkjet printer, online weighing instrument and other equipment to achieve linkage production;

Various automatic feeders and box-in systems can be designed according to packaging requirements;

According to customer requirements, hot-melt adhesive machine can be equipped with hot-melt adhesive spray sealing box and mechanical brush sealing box.

